# **AGNI HYDROPNEUMATIC PRIVATE LTD**

# Hydraulic Cylinder Catalogue

January 2025 Rev-01



# Welcome

Welcome to Agni Hydraulics Cylinders Catalogue, your source for high-performance hydraulic and pneumatic cylinders. We offer a comprehensive and cost competitive range of cylinders designed to meet the demands of diverse industries and applications.

Heavy Duty Hydraulic Cylinders Series – Custom Style Cynliders

Contact Us Address - AGNI Hydropneumatic Private Limited Plot No - 59A/5 Sector-04 IIE Sidcul Pantnagar Uttarakhand - 263153 Contact - 9045085537 | E-Mail - info@agnihp.com Website - https://agnihp.com





5.

# Table Of Content

*	Welcome 1
*	Contact Us
-	Table Of Content 2
*	Get to Know Our Company 3
	Material Information
*	Custom Style Cylinder 5

Contact us at info@agnihp.com or [click here] to visit our website.

5



## Get to Know Our Company

AGNI HYDROPNEUMATIC PRIVATE LIMITED newly established in 2024 as a small-scale firm, began its journey to introduce world-class Hydraulic and Pneumatic Cylinders of the latest design to the Indian market at affordable prices. Over the years, we will expand our product range to include Pneumatic Power Clamp Cylinders and Other Hydro-Pneumatic products like Valves, Connectors, Fittings and specialized products for OEM applications.

#### Our Mission

We aim to expand our range of products, technology, and customer base in the coming years to gain the same recognition in the international market and become a global company.

#### Our Vision

We are committed to enhancing industrial efficiency and performance by offering innovative, high-standard hydraulic and pneumatic solutions that meet the diverse needs of our clients nationwide

### **Our Values**

Customer-Centric It is our core value

that the Customer satisfaction comes before everything.

#### Innovative

We always strive to deliver new and better solutions to the ever changing business world.

#### Integrity

We are building trust with honesty and transparency is as the root of our value system

#### Involved

We value and are actively engaged with our customers, partners, employee or employees and the community.

#### Disclaimer Please Read The Following Warning Carefully

Please be aware that using the products described here incorrectly or for unsuitable applications

#### could lead to serious consequences, including death, injury, and property damage.

This document provides information for qualified users to explore product and system options. We encourage you to carefully analyze your specific application, including potential failure risks, and consult the current product catalog for detailed information.

**Agni Hydropneumatics** reserves the right to make changes to product features, specifications, designs, availability, and pricing without prior notice.

Ultimately, you are responsible for selecting the products and systems that best meet your needs and ensuring they comply with all performance, safety, and warning requirements. We appreciate your understanding and commitment to safety.



# Material Information

## Hard Chrome Plated Piston Rods

- ➤ Material : EN8D/CK-45
- > Chrome Thickness: 20-25 Micron Minimum per side above as per requirement.
- ➤ Tolerance: ISOf7/f8
- Plating Hardness: 850HV-1100HV
- Surface Roughness: Ra 0.2micon or better
- Straightness: 0.1mm per meter
- > UTS: 600-700 N/mm2 (min.)
- > Y.S: 450 N/mm2 (min)

## Hard Chrome Plated Piston Rods

- Material : ST52 in BK+S Condition and as per Customer
- ➤ Tolerance: As per ISO H8/H9
- Surface Roughness: Ra0.3micron Maximum
- ➤ T.S. :>580 N/mm2
- ➤ Y.S.: > 520N/mm2
- Elongation: >16%
- Straightness: 0.1mm per meter
- Packing Condition: Bore covered by cap and plastic and Transportation purpose M.S.plate welded in bore both sides

## Seal Matrials

4

5

Sr. No	Polytetrafluoroethylene	Polyurethane	Nitrile Butadiene Rubber
1	operating temp range: -200°C to 260°C	operating temp range : -40°C to 120°C	Operating temp range : -30°C and 100°C
2	PTFE's durability and chemical stability contribute to a longer lifespan compared to other sealing materials, especially in aggressive environments.	PU's elastic properties provide excellent shock absorption, beneficial in systems with frequent load and pressure changes.	NBR performs excellently with petroleum-based fluids and mineral oils, making it ideal for use in industrial hydraulic systems.
3	PTFE is inert to most chemicals, ensuring that the seals remain stable in a variety of hydraulic fluids, including aggressive and high-viscosity oils	PU seals can absorb impact loads and resist deformation, maintaining their shape and seal integrity under high pressure.	NBR has excellent resistance to petroleum-based oils, hydraulic fluids, and fuels, making it ideal for hydraulic applications.

PTFE's low friction coefficient results in smoother operations and reduced wear, especially important in systems with frequent or high-speed movements.

PTFE has a tendency to deform under prolonged high pressure, known as "cold flow" or "creep," especially in unreinforced forms. PU's flexibility allows a close fit, minimizing leakage and making PU seals suitable for high-precision applications. NBR has a low compression set, meaning it retains its shape well after being compressed, maintaining the integrity of the seal.

Standard PU is sensitive to water and may degrade in hydrolytic environments, so hydrolysis-resistant PU is necessary for water or glycol-based fluids.

NBR does not perform well with certain chemicals, such as strong acids, esters, ketones, and hydraulic fluids containing phosphate esters, as it can cause swelling and degradation.

4



# **Custom Style Cylinder**

To build Customized Cylinders,

We need a complete drawing of the custom cylinder

OR

## The following data:

- 1. Cylinder Outer Diameter or Required Tonnage.
- 2. Shaft Diameter and Piston Rod Threads
- 3. Working Length and Port Size.
- 4. Max operating Pressure Kgf/cm2
- 5. Cylinder Seal Material.

(For more info or any queries mail us at - info@agnihp.com or Click Here to visit our website.)



# **AGENIE** Hydraulics & Pneumatics

6

Address - AGNI Hydropneumatic Private Limited Plot No - 59A/5 Sector-04 IIE Sidcul Pantnagar Uttarakhand - 263153 Contact - 9045085537 | E-Mail - <u>info@agnihp.com</u> Website - <u>https://agnihp.com</u>